

Hydro-Brake® Drop

Energy Dissipating Flow Control



Protect your infrastructure from water hammer caused by dropping water from heights.

The Hydro-Brake® Drop is a self-activating energy dissipation system with no moving parts, designed to safely drop water or sewage from virtually any height in order to prevent noise, vibration, and infrastructure damage.

Benefits

- Self-activating with no moving parts
- Irithane coated components resist abrasion
- No air vents or auxiliary maintenance shafts
- Efficient, safe, controlled, and quiet
- Flexible design can accommodate multiple pipes in a single structure
- Fully enclosed system aids visual inspection to facilitate maintenance
- No de-aeration chamber needed

Applications

- Controlled drop of flow into deep tunnels
- Odor and corrosion control
- Flood control
- Combined / sanitary sewer systems
- Stormwater systems

Performance

- Design allows up to three (3) times the flow of a traditional drop shaft in the same pipe size

How it Works


Flows enter the system via the main horizontal inlet, around the carefully designed top bend and, if appropriate, taper. After dropping the desired height, flow enters into the Energy Dissipation Unit before continuing downstream.

The Hydro-Brake® Drop uses a unique Air Switch to enable a safe transition into the full pipe mode where it can operate at maximum capacity without the need for an air core. This allows it to accommodate as much as three times the flow as compared to a traditional drop shaft solution in the same pipe size.

The Hydro-Brake® Drop system's simple design facilitates easy retrofit into existing chambers while its integrated access and small pipe sizes reduce excavation cost and shaft diameters and eliminate the need for a separate access / vent shaft. The system also benefits from a compact and simple to construct inlet chamber with no complicated curves or benching.

Odor & Corrosion Control

The Hydro-Brake® Drop unit's wide range of operation in the air entrained flow mode combined with the enhanced and powerful mixing at the outlet by the energy dissipation unit ensures rapid oxidation of flow to prevent the release of noxious gases such as H₂S.



Small Pipe Size Results in Cost Savings

Traditional vortex drop shaft designs require the preservation of a finite sized air core while maintaining a specific terminal velocity of the water over a wide range of flows for proper operation. The resulting effect is oversized drop shafts with complicated influent structures and separate air vents to transfer entrained air out of the structure.

Key Components

Air Switch - Controls the amount of air entering into the falling flow from the Drop Pipe to eliminate 'glugging' and therefore the damaging effects of water hammer or hydraulic shock.

Top Bend - Safely transitions the flow into the vertical section of the pipe. A taper may be required depending on site circumstances.






Drop Structure - A full depth chamber housing the Drop Pipe, a control weir, maintenance access and the outlet structure

Energy Dissipation Unit - Developed using the latest scientific techniques, this component is designed to disperse the energy created by falling water in addition to effectively preventing erosion and controlling the onward flow.

Modes of Operation

Air Entrainment Mode

At low flow water passes through the Hydro-Brake® Drop inlet pipe and drops as a film, maintaining contact with the inside surface of the drop pipe. This results in the formation of a central air core through the drop pipe. Water then enters the top of the Energy Dissipation Unit and exits the system through the side openings into the bottom of the drop chamber. A weir at the bottom of the chamber creates a stilling area to absorb the release of energy from the water exiting the Energy Dissipation Unit. This ensures a smooth operation with minimal turbulence. At increased flows, the water level in the inlet chamber submerges the inlet pipe of the Hydro-Brake® Drop. At this stage, air is fed into the Hydro-Brake® Drop via the Air Switch, maintaining the stability of the air core and a smooth flow regime.



Energy Dissipation Unit
during Pipe Full Mode



Energy Dissipation Unit
during Air Entrainment Mode


Hydro-Brake® Drop Design

Configuration

The Hydro-Brake® Drop is completely configurable and can be designed to suit either the smallest flow or the longest drop. Its compact nature means that two or more shafts can fit into the same chamber, further enhancing its versatility and ensuring the best solution can be found for each project.

Construction

The Hydro-Brake® Drop is constructed from durable and corrosion resistant stainless steel. Furthermore the inlet bend, reducer, and Energy Dissipation Unit are treated with an Irlathane coating to protect them from wear and ensure an extremely long component life.



Learn more

To learn more about how the **Hydro-Brake® Drop** can help, visit hydro-int.com, or contact us:

Americas

1 (866) 615 8130
questions@hydro-int.com

Asia Pacific

+61 436 433 686
enquiries@hydro-int.com

Europe & RoW

+44 (0)1275 878371
enquiries@hydro-int.com

Middle East

+971 506 026 400
enquiries@hydro-int.com